



NOTES:

1. A.D.A. REGULATORY SIGNS SHALL BE M.U.T.C.D. #R7-801 AND #R7-801A (VAN ACCESSIBLE).
2. SIGN POST SHALL BE 2"x2" SQUARE STEEL POSTS, MIN. 14 GA. WITH 7/16" DIE-PUNCHED KNOCKOUTS ON 1" CENTERS FULL LENGTH ON ALL FOUR SIDES.
3. FOR HARD SURFACE INSTALLATIONS, CORE 4" DIA. HOLE. ANCHOR LENGTH MAY BE DECREASED TO 12".
4. POST SHALL BE ROLLED CARBON SHEET METAL STEEL, SHALL MEET REQUIREMENTS OF ASTM A653 GRADE 50, AND SHALL BE HOT DIPPED GALVANIZED IN ACCORDANCE WITH ASTM A653, G90, STRUCTURAL QUALITY GRADE 50.
5. ANCHOR SHALL HAVE FOUR 7/16" DIA. HOLES, ONE EACH SIDE, 2" FROM TOP END. ANCHOR SHALL MEET REQUIREMENTS OF ASTM A500 GRADE B AND SHALL BE HOT DIPPED GALVANIZED.
6. DRIVE RIVETS TO BE TL3806 3/8" DIA.
7. CORNER BOLTS TO BE TLCB516M
8. SIGN HEIGHT SPECIFIED ON THIS DETAIL DOES NOT APPLY TO OTHER REGULATORY SIGNS.



City of
Bellevue

TITLE:

SIGN - PARKING LOT - A.D.A. PARKING STALL

DRAWING #:	PK-SI-23
SCALE:	N.T.S.
REVISION DATE:	12-2018
DEPARTMENT:	PARKS