



MATERIALS LIST

- (A) PRESSURE REGULATOR ZURN/WILKINS 600XL-HLR-SC OR APPROVED EQUAL (LEAD-FREE WITH SEALED CAGE, INTERNAL BYPASS AND STRAINER).
- (B) BRONZE BALL VALVE, THREADED.
- (C) NIPPLE x 2 1/2" LONG, MALE.
- (D) UNION, FEMALE.
- (E) ADAPTER, FEMALE x COMPRESSION FITTING FOR COPPER.
- (F) METER BOX IN LANDSCAPING: CARSON INDUSTRIES 1730-18 BCF BOX. FLUSH COMPOSITE OR DUCTILE IRON COVER (CARSON, FIBRELYTE FL36, OR NICOR B36).

METER BOX IN SIDEWALKS AND AREAS WITH VEHICULAR TRAFFIC: OLYMPIC FOUNDRY SM30 BOX AND COVER, OR APPROVED EQUAL.

(G) 1" ROUND WASHED GRAVEL, 8" MIN. DEPTH.

NOTES:

- 1. PRESSURE REGULATOR SIZE AS SPECIFIED OR SHOWN ON PLAN.
- 2. SIZES FOR ITEMS (B) THROUGH (E) SHALL CORRESPOND TO THE SPECIFIED SIZE OF THE PRESSURE REGULATOR.
- 3. ALL FITTINGS AND NIPPLES ARE BRASS WITH IRON PIPE THREADS.



WATER UTILITY

TITLE

INDIVIDUAL PRESSURE REDUCING
VALVE ASSEMBLY
(MULTI-FAMILY OR COMMERCIAL) NO. W-21

JANUARY 2025

NO SCALE