



MATERIALS LIST

- (A) PRESSURE REGULATOR – ZURN/WILKINS 600XL-HLR-SC OR APPROVED EQUAL (LEAD-FREE WITH SEALED CAGE, INTERNAL BYPASS AND STRAINER).
- (B) BRONZE BALL VALVE, THREADED.
- (C) NIPPLE x 2 1/2" LONG, MALE.
- (D) UNION, FEMALE.
- (E) ADAPTER, FEMALE x COMPRESSION FITTING FOR COPPER.
- (F) METER BOX FOR 1" INSTALLATION:  
CARSON INDUSTRIES 1730-18 BCFXL WITH 1730 COVER, OR APPROVED EQUAL.  
FOR 1 1/2" & 2" INSTALLATION:  
CARSON INDUSTRIES 1730-18 BCFXL WITH 1730 COVER, OR APPROVED EQUAL.  
FOR ALL SIZE INSTALLATIONS:  
PROVIDE CARSON INDUSTRIES DUCTILE IRON COVER OR APPROVED EQUAL, IN LANDSCAPING. FOR SIDEWALKS AND AREAS WITH VEHICULAR TRAFFIC, PROVIDE OLYMPIC FOUNDRY SM-30 CAST IRON BOX & COVER, OR APPROVED EQUAL.
- (G) 1" ROUND WASHED GRAVEL, 8" MIN. DEPTH.

NOTES:

1. PRESSURE REGULATOR SIZE AS SPECIFIED OR SHOWN ON PLAN.
2. SIZES FOR ITEMS (B) THROUGH (E) SHALL CORRESPOND TO THE SPECIFIED SIZE OF THE PRESSURE REGULATOR.
3. ALL FITTINGS AND NIPPLES ARE BRASS WITH IRON PIPE THREADS.



City of  
Bellevue

WATER UTILITY

TITLE

INDIVIDUAL PRESSURE REDUCING  
VALVE ASSEMBLY

(MULTI-FAMILY OR COMMERCIAL) NO. W-21