




**Section 5. Fire Fighting Measures**

National Fire Protection Association (U.S.A.)



<b>Flash Point</b>	Closed cup: 51.6°C (125°F) [on liquid fill only]
<b>Flammable Limits</b>	Not available.
<b>Flammability</b>	Non-flammable. (CSMA Method)
<b>Fire hazard</b>	CONTENTS UNDER PRESSURE. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Bursting aerosol containers may be propelled from a fire at high speed.
<b>Fire-Fighting Procedures</b>	Use an extinguishing agent suitable for the surrounding fire. Cool closed containers exposed to fire with water. Fire-fighters should wear appropriate protective equipment.

**Section 6. Accidental Release Measures**

**Spill Clean up** Large spills are unlikely due to packaging.

**Section 7. Handling and Storage**

<b>Handling</b>	Put on appropriate personal protective equipment (see section 8). Store and use away from heat, sparks, open flame or any other ignition source. Avoid prolonged contact with eyes, skin and clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Observe label precautions. Wash contaminated clothing before reusing. Wash thoroughly after handling.
<b>Storage</b>	CONTENTS UNDER PRESSURE. Eliminate all ignition sources. Do not puncture, incinerate or store the container at temperatures above 49°C (120°F) or in direct sunlight. Keep out of the reach of children.

**Section 8. Exposure Controls/Personal Protection****Product name**

ODORLESS ALIPHATIC NAPHTHA; heavy alkylate petroleum naphtha; odorless mineral spirits

ISOPARAFFINIC SOLVENT; hydrotreated light distillate (petroleum)

PARAFFIN OIL; blend of heavy and light naphthenic petroleum distillate

HYDROCARBON PROPELLANT; blend of propane & isobutane

**Exposure limits**

**OSHA PEL (United States).**

TWA: 500 ppm 8 hour(s).

**ACGIH TLV (United States).**

TWA: 100 ppm 8 hour(s).

**NIOSH REL (United States).**

TWA: 1200 mg/m<sup>3</sup> Form: Vapor

**OSHA PEL (United States).**

TWA: 5 mg/m<sup>3</sup> 8 hour(s). Form: Mist

**ACGIH TLV (United States).**

TWA: 5 mg/m<sup>3</sup> 8 hour(s). Form: Mist

**ACGIH TLV / OSHA PEL (United States). Notes: Propane**

TWA: 1000 ppm 8 hour(s).

**Personal Protective Equipment (PPE)**

<b>Eyes</b>	Safety glasses.
<b>Body</b>	Recommended: Neoprene gloves. Nitrile gloves. Rubber gloves.
<b>Respiratory</b>	Use with adequate ventilation. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits.

**Section 9. Physical and Chemical Properties**

<b>Physical State</b>	Liquid. [Aerosol.]	<b>Color</b>	White Emulsion.
<b>pH</b>	Not applicable	<b>Odor</b>	Lemon-like.
<b>Boiling Point</b>	101.7°C (215.1°F)	<b>Vapor Pressure</b>	Not determined.
<b>Specific Gravity</b>	0.943	<b>Vapor Density</b>	Not determined.
<b>Solubility</b>	Insoluble in the following materials: cold water and hot water.	<b>Evaporation Rate</b>	Not determined.
		<b>VOC (Consumer)</b>	24.9% 1.96 (lb/gal) 234 (g/l).

**Section 10. Stability and Reactivity**

<b>Stability and Reactivity</b>	The product is stable.
<b>Incompatibility</b>	Reactive or incompatible with the following materials: oxidizing materials.
<b>Hazardous Polymerization</b>	Will not occur.
<b>Hazardous Decomposition Products</b>	carbon oxides (CO, CO <sub>2</sub> )

**Section 11. Toxicological Information****Acute Toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Odorless Aliphatic Naphtha	LD50 Oral	Rat	>18800 mg/kg	-
	LC50 Inhalation Vapor	Rat	>5900 mg/m <sup>3</sup>	4 hours
Isoparaffinic Solvent; Hydrotreated light distillate (petroleum)	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-

**Section 12. Ecological Information**

**Environmental Effects** No known significant effects or critical hazards.

**Aquatic Ecotoxicity**

Not available.

**Section 13. Disposal Considerations****Waste Information**

Waste must be disposed of in accordance with federal, state and local environmental control regulations. Consult your local or regional authorities for additional information.

**Waste Stream** Classification: - [Non-hazardous waste]

**Section 14. Transport Information**

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label
<b>DOT Classification</b>	Not regulated.	Consumer commodity ORM-D			
<b>TDG Classification</b>					
<b>IMDG Class</b>	Not determined.				

**NOTE:** DOT classification applies to most package sizes. For specific container size classifications or for size exceptions, refer to the Bill of Lading with your shipment.

PG\* : Packing group

**Section 15. Regulatory Information****U.S. Federal Regulations**

SARA 313 toxic chemical notification and release reporting:

**Product name**

Naphthalene  
Xylene

**Clean Water Act (CWA) 307:** No products were found.

**Clean Water Act (CWA) 311:** No products were found.

**Clean Air Act (CAA) 112 regulated toxic substances:** No products were found.

All Components of this product are listed or exempt from listing on TSCA Inventory.

**State Regulations**

**California Prop 65** No products were found.

**Canada****WHMIS (Canada)**

Class A: Compressed gas.

Class D-2B: Material causing other toxic effects (Toxic).

**Section 16. Other Information**

*To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.*

\*NOTE: Hazard Determination System (HDS) ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although these ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HDS ratings are to be used with a fully implemented program to relay the meanings of this scale.