



SECTION

ELEVATION

NOTES:

1. ALL LUMBER SHALL BE D.F. #2 OR BETTER, TREATED WITH ACQ/CBA, OR APPROVED EQUAL.
2. FASTENING HARDWARE TO BE #10 WOOD SCREWS, HOT DIPPED GALVANIZED OR STAINLESS STEEL, OR APPROVED EQUAL.
3. UNLESS OTHERWISE DIRECTED BY BELLEVUE PARKS, INSTALL DIAGONAL BRACE RAILING (4x4) AT ALL END AND CORNER SECTIONS WITH TOP OF BRACE AT TOP OF END SECTION/CORNER.
4. TOP CAP: SEEMS TO BE CUT AT 22.5°. EASE ALL EXPOSED EDGES ¼" RADIUS. JOINTS TO BE ALTERNATED WITH 2x4 HORIZONTAL RAIL JOINTS.
5. 16'x5' HOG WIRE PANELS: 0.25" DIA. GALV. ROD WIRING WITH 2"x4" MESH OPENINGS, OR APPROVED EQUAL.
6. THE HEIGHT BETWEEN FINISHED GRADE AND BOTTOM RAIL SHALL BE 6" WHENEVER POSSIBLE BUT MAY BE ADJUSTED AS NECESSARY ON SLOPED GRADES TO MAINTAIN LEVEL RAILS.



TITLE:  
**FENCE - BOARD WITH FABRIC - PICTURE FRAME  
 OPTION**

DRAWING #:	PK-FE-04C
SCALE:	N.T.S.
REVISION DATE:	01-2019
DEPARTMENT:	PARKS