



NOTES:

1. SUB-GRADE SHALL BE RIPPED AND TILLED TO A MIN. DEPTH OF 8 INCHES. REMOVE ALL FOREIGN DEBRIS AND ANY ROCK LARGER THAN 2 INCHES FROM SURFACE OF SUB-GRADE PRIOR TO THE INSTALLATION OF FIRST COURSE.
2. FOR GENERAL LANDSCAPE AREAS, FIRST COURSE SHALL CONSIST OF 3-WAY TOPSOIL. FOR SPORT FIELD APPLICATIONS (NON-SAND BASED), FIRST COURSE SHALL CONSIST OF 60% SAND AND 40% COMPOSTED ORGANIC MATERIAL BY VOLUME. SOILS SHALL BE THOROUGHLY MIXED OFFSITE AND DELIVERED TO PROJECT SITE IN LOOSE, BLENDED, WELL-GRADED MIX.
3. PLACE FIRST COURSE OF TOPSOIL ON EXISTING SUB-GRADE AND TILL INTERFACE TO A 4" MIN. DEPTH.
4. FINAL COURSE SHALL CONSIST OF 60% SAND AND 40% COMPOSTED ORGANIC MATERIAL BY VOLUME. SOIL SHALL BE THOROUGHLY MIXED OFFSITE AND DELIVERED TO PROJECT SITE IN LOOSE, BLENDED, WELL-GRADED MIX. FINAL COURSE SHALL BE GRADED AND COMPACTED SUFFICIENTLY ENOUGH TO PROVIDE STABLE AND UNIFORM SURFACE.
5. FARM GROWN SOD SHALL BE PERENNIAL RYE GROWN LOCALLY IN THE PACIFIC NORTHWEST REGION WITHIN A MEDIUM CONTAINING NO NETTING AND LESS THAN 15% CLAY CONTENT. SOD SHALL BE CUT FROM THE SUPPLIER'S FIELD, DELIVERED TO THE PROJECT SITE AND INSTALLED WITHIN A 48 HOUR WINDOW. SOD SHALL BE INSPECTED AND APPROVED BY BELLEVUE PARKS PRIOR TO INSTALLATION.
6. GRASS SEED AND/OR HYDROSEED SHALL BE A PERENNIAL RYE MIX CONTAINING NO LESS THAN 98% PURE RYEGRASS SEED AND NO MORE THAN 0.5% WEED SEED.



**City of
Bellevue**

TITLE:

PLANTING - TURF

DRAWING #:	PK-IM-05A
SCALE:	N.T.S.
REVISION DATE:	12-2018
DEPARTMENT:	PARKS